



LumaPro Spot

10, 16, 24 watt LED Track Spot
IP20 | 24°, 36°, 52° Beam Angle | Track Mount

Application

A solution for Commercial, Retail, Education and Hospitality areas.

Features


- Input Voltage: AC220-240V, 50/60Hz
- Luminaire Efficacy: 130lm/W
- Power Consumption: 10W | 16W | 24W
- Rated Voltage: AC220-240V
- CCT: 3000K-3500K-4000K
- Power Factor: ≥ 0.9
- LED Type: COB
- Driver Type: Tridonic / Vossloh-Schwabe / Eaglerise
- Unified Glare Rate: < 19
- Colour Consistency: SDCM ≤ 3
- Electrical Class I
- Surge Protection: 1.5kv
- Lumen Maintenance: L80 B10 @ 50 000hrs
- Operational Lifespan: 50 000hrs
- Track Mount - 3 Circuit (4 wire)



Design Specifications

- Housing Body: Die-Cast Aluminium
- Diffuser: Tempered Glass Lens.
- Housing Colour: White | Black
- Driver Placement: In track

Angle Adjustment



Performance



Model No.	Dimensions (mm)	Power	Efficacy lm/W	CCT (K)	CRI	Beam Angle
LUM00244	Ø100*100	10W 16W 24W	130	3000K	>90	24° 36° 52°
LUM00245	Ø100*100	10W 16W 24W	130	3500K	>90	24° 36° 52°
LUM00246	Ø100*100	10W 16W 24W	130	4000K	>90	24° 36° 52°

LumaPro Spot



Certifications



Unit 21 & 22, Brentwood Office Park,
Brentwood Park AH, Benoni.
info@lambdalumen.com
Tel: +27 10 500 9150