




LED TUBES

8-30 watt LED area luminaire
IP20 | 30°, 60°, 120° Beam Angle | T8 | T5 Mount

Application

A solution for residential, commercial, retail, Industrial, Education and Hospitality areas.




Features

- Luminaire Efficacy: 110-190lm/W
- Rated Voltage: AC110-265V , 50/60Hz
- CCT: 3000K-4000K-6000K
- Power Factor: ≥ 0.9
- LED Type: SMD 2835
- Unified Glare Rating: UGR >16
- Colour Consistency: SDCM <4
- Electrical Class: I
- Colour Rendering Index: >80 | >90
- Lumen Maintenance: L80 B10 50 000hrs
- Operational lifespan: 50 000hrs
- Operating Temperature: -20°C ~ 50°C


Design Specifications

- Housing Body: Aluminium.
- Lens Diffuser: Polycarbonate.
- Lens: Clear/Frosted
- Tube Size: T8 | T5

Dimensions



Photometric Data



Performance



Wide Beam

Narrow Beam

LED TUBES

8-30 watt LED area luminaire
IP20 | 30°, 60°, 120° Beam Angle | T8 | T5 Mount

Technical Specifications

Model No.	Dimensions (mm)	Power	Efficacy lm/W	CCT (K)	CRI	Beam Angle	UGR	SDCM
TUB-T8-01	2FT	8W	130	4000K	>80	120°	>16	<4
TUB-T8-02	2FT	9W	130	4000K	>80	120°	>16	<4
TUB-T8-03	3FT	14W	130	4000K	>80	120°	>16	<4

Model No.	Dimensions (mm)	Power	Efficacy lm/W	CCT (K)	CRI	Beam Angle	UGR	SDCM
TUB-T8-04	4FT	14W	130	4000K	>90	120°	>16	<4
TUB-T8-05	4FT	15W	130	4000K	>90	120°	>16	<4
TUB-T8-06	4FT	17W	130	4000K	>90	120°	>16	<4
TUB-T8-07	4FT	20W	130	4000K	>90	120°	>16	<4
TUB-T8-08	4FT	22W	130	4000K	>90	120°	>16	<4
TUB-T8-09	4FT	23W	130	4000K	>90	120°	>16	<4
TUB-T8-10	4FT	26W	130	4000K	>90	120°	>16	<4
TUB-T8-11	4FT	27W	130	4000K	>90	120°	>16	<4
TUB-T8-12	4FT	30W	130	4000K	>90	120°	>16	<4

Model No.	Dimensions (mm)	Power	Efficacy lm/W	CCT (K)	CRI	Beam Angle	UGR	SDCM
TUB-T8-13	5FT	14W	130	4000K	>90	120°	>16	<4
TUB-T8-14	5FT	16W	130	4000K	>90	120°	>16	<4
TUB-T8-15	5FT	17W	130	4000K	>90	120°	>16	<4
TUB-T8-07	5FT	20W	130	4000K	>90	120°	>16	<4
TUB-T8-08	5FT	22W	130	4000K	>90	120°	>16	<4
TUB-T8-09	5FT	23W	130	4000K	>90	120°	>16	<4
TUB-T8-10	5FT	26W	130	4000K	>90	120°	>16	<4
TUB-T8-11	5FT	27W	130	4000K	>90	120°	>16	<4
TUB-T8-12	5FT	30W	130	4000K	>90	120°	>16	<4

LED TUBES



Certifications



Optional Features

- Dimmable Options
- Luminaire mountable sensors available
- Emergency options are available on request.



Unit 21 & 22, Brentwood Office Park,
Brentwood Park AH, Benoni.
info@lambdaalumen.com
Tel: +27 10 500 9150