



LUMA TRACK SPOT

25, 35 watt LED Track Spot
IP20 | 15°, 24°, 36°, 60° Beam Angle | Track Mount

Application

A solution for Commercial, Retail, Education and Hospitality areas.

Features


- Input Voltage: AC220-240V, 50/60Hz
- Luminaire Efficacy: 120 | 160lm/W
- Power Consumption: 25W|35W
- Rated Voltage: AC220-240V
- CCT: 3000K-4000K-5000K
- Power Factor: ≥ 0.9
- LED Type: COB
- Driver Type: Tridonic/VosslohSchwabe/ALLOOKING/KGP/OKESUN
- UGR<19
- SDCM ≤ 3
- Electrical Class I
- Surge Protection: 1KV
- L&B Rating: L80 B10 @ 50 000hrs
- Lifespan: 50 000hrs
- Track Mount - 3 Circuit (4 wire)

Design Specifications


- Die-Cast Aluminium Housing Body
- Tempered Glass Lens Diffuser.
- White | Black Housing Colour
- In track driver
- High uniformity ratio.
- Low glare ratio (UGR<19)



Dimensions



Angle Adjustment



Performance



Model No.	Dimensions (mm)	Power	Lumen lm/W	CCT (K)	CRI	Beam Angle	UGR	SDCM
LUM00103	Ø100*100	25W	120	4000K	>90	15° 24° 36° 60°	19	≤ 3
LUM00104	Ø100*100	35W	120	4000K	>90	15° 24° 36° 60°	19	≤ 3

LUMA TRACK SPOT



Certifications



Optional Features

- Triac | 0-10V | DALI Dimmable Options.
- Optional Sensors Available.
- Optional Honeycomb louver, In track Driver, CRI90
- Emergency Backup available on request.



Unit 21 & 22, Brentwood Office Park,
Brentwood Park AH, Benoni.
info@lambdalumen.com
Tel: +27 10 500 9150