



OPTILINE T12

24 | 60 watt LED area luminaire
IP20 | 120° Beam Angle

Application

A solution for residential, commercial, retail, industrial, education and general areas.

Features

- Input Voltage: AC220-240V, 50Hz
- Luminaire Efficacy: 170lm/W
- CCT: 4000K | 5000K
- Power Factor: >0.98
- Electrical Class I
- Beam Angle: 120° (Diffuser)
- Operating Temp: 0°C ~ 40°C
- Total Harmonic Distortions: ≤15%
- Colour Rendering Index: ≥80
- Lifespan: 50 000hrs



Accessories

Design Specifications

- Material: Polycarbonate
- Enclosed External Driver
- Flicker free
- True seamless



- T-Piece
- 90° Band
- Cross Piece
- Mounting Clips

Performance



Technical Specifications

Model No.	Dimensions (mm)	Power	Lumen lm/W	CCT (K)	CRI	Beam Angle	Color
OL000156	1800mm	60W	170lm/W	4000K	≥80	120°	White
OL000157	1800mm	60W	170lm/W	5000K	≥80	120°	White
OL000158	900mm	24W	170lm/W	4000K	≥80	120°	White
OL000159	900mm	24W	170lm/W	5000K	≥80	120°	White

OPTILINE T



Certifications



Optional Features

- Dimmable Options.
- Sensor Options.
- Emergency options are available on request.



Unit 21 & 22, Brentwood Office Park,
Brentwood Park AH, Benoni.
info@lambdalumen.com
Tel: +27 10 500 9150