

SUSPENDED EXIT LIGHT

3 watt LED exit light
IP30 | Surface Mount

Application

A solution for industrial, tunnels, hotels, airports, malls, retail and commercial areas.

Features

- Rated Voltage: 220V-240V, 50Hz
- Input Voltage: AC184-265V
- 1.5hrs-3hrs backup
- Correlated Color Temperature: 6000K
- Power Factor: ≥ 0.95
- LED Type: SMD 2835
- Luminaire Efficacy: 12lm/W
- Electrical Class I
- Operating Temperature: $-20 \sim 50^{\circ}\text{C}$
- Luminance of Safety Sign: $>15\text{cd}/\text{m}^2$
- Size: 360*208*20mm
- Viewing Distance: 30 Meters
- Lifespan: 50 000hrs
- Charge Time: 24 hours
- Discharge Duration: 1 | 2 | 3 hours
- Test Facility: Button Self Test | Auto Self-Test
- Operation: Maintained | Non-Maintained | ACEG

Design Specifications

- Housing Body: ABS Housing Injected Moulded Thermoplastic
- Frame: Aluminium & Acrylic Cold Rolled Steel Sheet
- Housing Colour: White
- Lithium Battery/Nicd/NiMH/Li-ion


Performance



Battery Features

- Battery Type: Li-ion
- Specifications: 1.2V NiCd 700mA

Dimensions



Technical Specifications

Model No.	Dimensions (m)	Power	CCT (K)	IP	Input Voltage
ES000168	360*208*20	3W	6000K	30	AC184-265V

EXIT LIGHT - SUSPENDED MOUNT



Certifications



Unit 21 & 22, Brentwood Office Park,
Brentwood Park AH, Benoni.
info@lambdalumen.com
Tel: +27 10 500 9150